

2 trick

## **AUTOMATIC·SEMIAUTOMATIC**

2 gr compact • 2 gr • 3 gr



With Digit Chrono and pre-infusion setting.

It is dedicated to those ethnic and folk musics, in which we research more and more an historical identity, as they always maintain their originality of sound, of melodies and materials of their instruments.











## **AUTOMATIC·SEMIAUTOMATIC**

2 gr compact • 2 gr • 3 gr

Strumenti per l'Espresso

TECHNICAL FEATURES	AUTOMATIC		SEMI Automatic			
Espresso coffee and cappuccino machine with thermosiphonic system	2gr comp	2gr	3gr	2gr comp	2gr	3gr
Connectability to external display (by Orchestrale distributor technician) for pre-infusion setting and other display functions	•	•	•	0	0	0
E 61 brewing groups (filter holder Ø 58 mm)	•	•	•	•	•	•
Frame of pure polished super-mirror and satined stainless steel AISI 304. Finishing of transparent methacrylate	•	•	•	•	•	•
Flanged (2 gr. compact excluded) boiler of copper with tap for manual discharge, pipes of copper and pipe fittings of brass	•	•	•	•	•	•
Dual gauges for boiler and pump pressure	•	•	•	•	•	•
Manual and automatic boiler water loading	•	•	•	•	•	•
Programmable portion control / Single group washing	•	•	•	0	0	0
Built-in RPM motor pump with <b>water</b> cooling / Fluid-o-Tech rotary pump	•	•	•	•	•	•
Touchpad for each group with pilot lights for activated brewing buttons:			•	0	0	0
6 volumetric metering selections programmable from the touchpad directly and 1 programming button					0	0
1 electromechanical button for every group for brewing choice (only for 2 groups in the 3 groups version)	•	•	•	•	•	•
Indicator to inform that machine and cup heater are ON	•	•	•	•	•	•
LED lights on the back panel (with ON/OFF switch)	•	•	•	•	•	•
Electric cup heater (with ON/OFF switch) with programmable working temperature	• • •		optional			
Digit Chrono	0	•	•	0	0	0
LED indicator for boiler water level (filling - level reached - timeout)	0	•	•	0	0	0
Glass tube for boiler water level	0	0	0	0	•	•
1 multidirectional stainless steel steam wand with manual control from the tap knob	•	0	0	•	0	0
2 multidirectional stainless steel steam wands with manual control from the tap knobs	0	•	•	0	•	•
1 multidirectional stainless steel hot water wand with manual control from the tap knob	•	0	0	•	0	0
1 multidirectional stainless steel hot water wand with manual control from its dedicated button	0	•	•	0	•	•
OPTIONAL ON DEMAND						
Electric cup heater (with ON/OFF switch) with programmable working temperature	st	tandar	d	•	•	•
Mixed hot water outlet	0	•	•	0	0	0
External motor pump (air cooling)	•	•	•	•	•	•
Raised groups	•	•	•	•	•	•
Cappuccino maker / Milk frothing wand	•	•	•	•	•	•
GAS Kit	0	0	0	0	•	0
Serial interface for external connection to the cash register	•	•	•	0	0	0
· · · · ·						-

TECHNICAL DATA		2 gr compact	2 gr	3 gr		
Voltage/Power	120 V (1F)	2600 - 2930 W	2600 - 2930 W			
	220 - 240 V (1F) / 380 - 415 V (3F)	3000 - 6650 W	3000 - 6650 W	4500 - 6700 W		
Frequency	Hz	50 - 60				
Boiler	Lt	7	12	17		
Length	mm	530	740	980		
Width	mm	600				
Height	mm	560				
Net weight	Kg	60	64	95		



White filter holders for 1 and 2 cups

Nut wood kit: filter holders and knobs

Color options and aesthetic customisation

•

•

•

•

•

.

•