



Strumenti per l'Espresso

*etnica* Display **TT**

**AUTOMATIC**  
2 gr • 3 gr



Optional:  
LED cup lighting,  
black matt sides and  
electronic injection autosteamer

With touchpads above the groups and joystick taps,

it's a variation of Etnica Display still automatic, with enclosed groups and display, it carries forward the same spirit as the Etnica Display: it embodies the timeless bond between past and future, where history gives birth to innovation, and cutting-edge technology harmonizes with the sounds and soul of a bygone era.



TECHNICAL FEATURES	AUTOMATIC	
	2gr	3gr
Espresso coffee and cappuccino machine with thermosiphon system		
E 61 brewing groups (filter holder Ø 58 mm)	•	•
Frame of pure polished super-mirror and satin-finished stainless steel AISI 304. Finishing of transparent methacrylate	•	•
<b>Flanged</b> copper boiler with tap for manual discharge, copper pipes and brass pipe fittings	•	•
Dual gauges for boiler and pump pressure	•	•
<b>Manual</b> and <b>automatic</b> boiler water loading	•	•
Programmable portion control / Single group washing	•	•
Built-in RPM motor pump with <b>WATER</b> cooling / Fluid-o-Tech rotary pump	•	•
Touchpad for each group with pilot lights for activated brewing buttons:	•	•
6 volumetric metering selections programmable from the touchpad directly and 1 programming button		
1 electromechanical button for every group for brewing choice (only for 2 groups in the 3 groups version)	•	•
Indicator to inform that machine and cup heater are ON	•	•
LED lights on the back panel (with ON/OFF switch)	•	•
<b>Electric cup heater (with ON/OFF switch) with programmable working temperature</b>	•	•
Glass tube for boiler water level	•	•
2 multidirectional stainless steel steam wands with manual control from the <b>joystick taps</b>	•	•
1 multidirectional stainless steel hot water wand with manual control from its dedicated button	•	•

ALPHAMERIC DISPLAY	After the switch-on it displays the functional test and malfunction notice, boiler filling, filling timeout. It displays boiler filling also when the boiler refills. When the machine is in use, after the functional test the alphanumeric display shows always the boiler temperature and pressure, hour, date, number of the weekday.
<b>allows to plan/program:</b> CLOCK SETUP: hour, date, number of the weekday AUTO ON/OFF: switching ON/OFF time of the machine WORKING DAYS: coffee shop day off DELIVERY TEST CRONO: brewing time (digit chrono) CUP HEATER: cup heater working temperature AUTOSTEAMER: autosteamer temperature REGEN. SOFTENER: water litres to regenerate the softener CHANGE PASSWORD: new password to get access to the display functions	<b>allows to display:</b> PREINF. SINGLE: pre-infusion time for single and double coffee WASHING GROUP IN PROGRESS: single group washing MAINTENANCE: number of coffee to the next maintenance LANGUAGE: ENGL-CEL, ENGL-FAH, ITALIANO, FRANCAIS, DEUTSCHE, ESPANOL, PORTUGUES COUNTER LITERS: total used litres of water DOSER ALARM: flowmeter malfunction times TOTAL COFFEES: total coffee done with the automatic touchpad from installation BOILER PRESSURE: boiler pressure

OPTIONAL ON DEMAND		
Mixed hot water outlet	•	•
External motor pump (air cooling)	•	•
Raised groups	•	•
Cappuccino maker / Milk frothing wand	•	•
<b>Electronic injection autosteamer with adjustable control of speed and of pump capacity. Wand with directing holes for an elliptical steam brewing</b>	•	•
Serial interface for external connection to the cash register	•	•
<b>LED</b> cup lighting	•	•
White filter holders for 1 and 2 cups	•	•
Nut wood kit: filter holders and knobs	•	•
<b>Color options and aesthetic customisation</b>	•	•

TECHNICAL DATA		2 gr	3 gr
Voltage/Power	120 V (1F)	2600 - 2930 W	
	220 - 240 V (1F) / 380 - 415 V (3F)	3000 - 6650 W	4500 - 6700 W
Frequency	Hz	50 - 60	
Boiler	L	12	17
Width	mm	740	980
Depth	mm	600	
Height	mm	560	
Net weight	kg	65	96