



Strumenti per l'Espresso

radiofonica

AUTOMATIC
2 gr



Full optional



AUTOMATIC

2 gr

Strumenti per l'Espresso

TECHNICAL FEATURES	AUTOMATIC
Espresso coffee and cappuccino machine with thermosiphon system	2gr
E 61 brewing groups (filter holder Ø 58 mm) with 1 PURGE button per group	●
Body of satin-finished stainless steel AISI 304	●
Copper boiler with tap for manual discharge, copper pipes and brass pipe fittings	●
Dual gauges for boiler and pump pressure	●
Automatic boiler water loading	●
Programmable portion control / Single group washing	●
Built-in RPM motor pump with AIR cooling / Fluid-o-Tech rotary pump	●
Waterproof silicone touchpad for each group with 16 mm diam. pushbuttons:	●
4 volumetric metering selections programmable from the touchpad directly, 1 programming/continuous coffee button and 1 hot water button	●
LED lights on the back panel	●
Glass tube for boiler water level	●
2 multidirectional stainless steel steam wands with manual control from the joystick taps	●
1 multidirectional stainless steel hot water wand with manual control from its dedicated button on the touchpad	●



OPTIONAL ON DEMAND	
Alphanumeric Display	●
Digit Chrono	●
LED cup lighting	●
White filter holders for 1 and 2 cups	●
Nut wood kit: filter holders and knobs	●
Color options and aesthetic customisation	●

ALPHAMERIC DISPLAY	After the switch-on it displays the functional test. It displays boiler filling also when the boiler refills. When the machine is in use, after the functional test the alphanumeric display shows always hour.
allows to plan/program:	
CLOCK SETUP, AUTO ON/OFF, WORKING DAYS, DELIVERY TEST CRONO, DOSE SETTING, NUMBER OF COFFEES, REGENERATION SOFTENER, SERVICE, WASHING GROUP IN PROGRESS, LANGUAGE, NAME OF COMPANY, SERVICE PHONE, CHRONO FUNCTION, ON/OFF TOUCHPAD BUTTONS LED LIGHTS IDLE, KEYBOARD TYPE, FILLING UP + COFFEE, CONTINUOUS KEY, PREINFUSION SINGLE, PROBE SENSITIVITY, FILLING UP TIME-OUT	
allows to display:	
COUNTER LITERS, TOTAL COFFEES	

TECHNICAL DATA	2 gr
Voltage/Power	220 - 240 V (1F) / 380 - 415 V (3F)
Frequency	Hz
Boiler	L
Width	mm
Depth	mm
Height	mm
Net weight	kg

D.I.D. srl reserves the right to modify the appliances presented in this publication without notice.